



Architectural Grade High Power 17 Watt Dimmable Led Replacement Lamp

Produces 90 Watts of Incandescent Halogen Light

LM-79 and LM-80 Tested

- Robust electronics mounted to a layered (redundant) heat dissipation substrate
- Proprietary optics deliver light to the task
- **Finishes: White, Black, Custom**
- Instant On, No Warm Up, No Flicker
- May Be Controlled by Peripheral Systems and Sensors
- Five Year Hassle Free Warranty
- Generous Beta Test Programs
- Reduced waste – contractor and earth-friendly packaging for roll-outs and projects

Life Rating Reduced +/- 15% When Used in IC Housings.
Do Not Use in Enclosed Fixture.

*Compatible dimmer models Lutron TG-600PH-LA, MRF-2-6ELV; HW/LP-RPM-4A-120; HW/LP-RPM-4U-120; GP (Harrier) Card; HxD-SNE; Grafik Eye QS Main Unit Family; RRD-6NA; PHPM-PA with QSG-D; Leviton 6633-P (consult factory for updated list)

Family	Product	Field	Color Temp	Finish
DL	P38F	38	27K	WH
		60	30K	BL

Beam Angle 50%	17°	35°
Field Angle 10%	38°	60°
Power Consumption	17 Watts	
Equivalent Source	90W	
Power Factor	>0.80	
Dimming Range*	20-100%	
Color Temperature	2700K (Warm White) 3000K (Natural White)	
CRI	80+	
Lumen Output	870	810
Lumens/Watt (Typ)	57	55
CBCP	7110	2000
Operating Temp	-20 ~ +40°C	
Storage Temp	-40 ~ +60°C	
AC Input Voltage	120 Volts	
Lumen Maintenance	L70 >50,000 Hours	
Environmental	Contains no lead or mercury No UV or IR emmissions	
Warranty	5 years	
Use	Indoor applications	
Weight	500 grams ±5	
Dimensions	4.75"W x 4.75"H	
Base	E26	

